

# SAFETY DATA SHEET

# **SECTION 1: IDENTIFICATION**

Manufacturer:

General Shale Brick, Inc. P.O. Box 3547 Johnson City, TN 37602 (423) 282-4661 **Product Name:** Concrete Block, Lintels, Pavers, Regency, Concrete Veneers, and Retaining wall products

Chemical Family/Name: Silicon Dioxide, Concrete/Aggregate

Formula: Mixture

Emergency Info: (423) 952-4205

Product Use: Masonry building material/component

# SECTION 2: HAZARD(S) IDENTIFICATION





#### SIGNAL WORD: Warning

Concrete products as shipped do not present an inhalation, ingestion or contact hazard. However, operations such as sawing and grinding may result in the following effects.

# ACUTE EFFECTS OF OVEREXPOSURE:

#### **Contains Crystalline Silica**

Eye: May cause irritation by abrasion with dust or chips.

Skin: Concrete dust or chips may cause allergic reactions in hypersensitive individuals; May cause cuts and skin abrasions.Inhalation: Brick dust or chips may cause congestion and irritation in nasal and respiratory passages.Ingestion: No known acute effects.

#### CHRONIC EFFECTS OF OVEREXPOSURE:

Excessive exposures to respirable particulates (dust) over an extended period of time may result in the development of pulmonary diseases such as silicosis.

# **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Common Name	Chemical Name	CAS#	% Weight	Exposure	e Limits		
Silica / Quartz Flint Sand	Silicon Dioxide			OSHA PEL mg/m <sup>3</sup>	ACGIH TLV mg/m <sup>3</sup>		
Crystalline Free Silica		Various	50 – 85	15	10		
Other Limits Recommended: National Institute for Occupational Safety and Health (NIOSH). Recommended standard maximum permissible concentration = $0.05 \text{ mg/M}^3$ (respirable free silica) as determined by a full-shift sample up to 10-hour work week. See NIOSH Criteria for a Recommended Standard Occupational Exposure to Crystalline Silica.							



Concrete Masonry Products Date Completed: 01/05/2011 Latest Revision: 07/24/2015 Initiator: Safety Office

#### **SECTION 4: FIRST-AID MEASURES**

**Inhalation:** Remove from exposure to airborne particulates. Consult a physician if breathing does not return to normal. **Skin:** Wash with soap and water. If an allergic reaction causes a rash that does not heal within a few days consult a physician. Treat abrasions as any other scrape or cut with disinfectants and bandages.

Eye: Flush with running water. Obtain medical assistance if irritation continues.

**Medical Conditions Aggravated by Exposure:** Excessive dust exposure may aggravate any existing respiratory disorders or diseases. Possible complications or allergies resulting in irritation to skin, eyes, and respiratory tract may occur from excessive exposure to dusts. Dry sawing or grinding of concrete masonry products may result in the release of respirable crystalline quartz. Prolonged exposure to respirabel crystalline quartz may cause delayed (Chronic) lung injury (Silicosis). Acute or rapidly developing silicosis may occur in a short period of time in heavy exposure. Silicosis is a form of disabling pulmonary fibrosis, which can be progressive and may lead to death.

#### **SECTION 5: FIRE FIGHTING MEASURES**

Bricks as shipped do not pose a fire or explosion hazard.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Brick as shipped do not present a human or environmental hazard that requires special clean-up measures.

# **SECTION 7: HANDLING AND STORAGE**

Provide adequate ventilation to maintain exposures below the OSHA PEL and ACGIH TLV for quartz and other substances.

# SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection:	For airborne concentration exceeding the OSHA PEL or ACGIH TLV use a NIOSH and/or MSHA		
	approved respirator.		
Eye and Face:	Face shields should be used when sawing brick.		
Skin:	Use gloves and or protective clothing if abrasions or allergic reactions are experienced.		
Other:	Use of steel toe shoes is recommended when handling brick.		
Other Controls:	Use of wet sawing methods is recommended anytime that bricks must be cut.		
<b>SECTION 9: PHYSICAI</b>	AND CHEMICAL PROPERTIES		
Boiling Point: NA	Melting Point: NA	Specific Gravity: 2.6	

0	0	1 1
Vapor Pressure: NA	Vapor Density: NA	Soluble in Water: Negligible

Appearance and Odor: Granular solid, essentially odorless. Bricks come in a wide range of colors.

### SECTION 10: STABILITY AND REACTIVITY

Bricks as shipped are not reactive.

#### SECTION 11: TOXICOLOGICAL INFORMATION

**CARCINOGENICITY:** The following carcinogenicity classifications for crystalline silica have been established by the following agencies:

**OSHA:** Not regulated as a carcinogen

IARC: Group 1 carcinogenic in humans

NIOSH: Carcinogen, with no further categorization

NTP: Known carcinogen

WARNING: Brick dust may contain crystalline silica, a chemical that has been determined by the agencies listed above to cause cancer.



# **SECTION 12: ECOLOGICAL INFORMATION**

No data is currently available.

# SECTION 13: DISPOSAL CONSIDERATIONS

Brick in its solid form is typically considered a non-hazardous waste for disposal, but local regulation may vary, therefore all waste must be disposed/recycled/reclaimed in accordance with federal, state, and local environmental control regulations. Water containing brick solids, such as from wet sawing operations, should also be disposed of in accordance with federal, state and local environmental regulation. Brick waste should not be used as a blasting agent.

#### **SECTION 14: TRANSPORT INFORMATION**

DOT Shipping Name: Not regulated by DOT

DOT Hazard Class:

Identification Number:

Canada TDG: Not regulated by TDG.

Hazard Class:

**UN Number:** 

# **SECTION 15: REGULATORY INFORMATION**

RCRA: Bricks as shipped are not hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA).

**SARA/EPCRA:** Bricks as shipped are not hazardous substances subject to the federal Emergency Planning and Community Right to know Act (EPCRA) for inventory reporting (SARA 311/312), nor Toxic Release Inventory (SARA 313).

**DOT:** Bricks as shipped are not hazardous materials per Department of Transportation (DOT) regulations.

#### **SECTION 16: OTHER INFORMATION**

We recommend only wet sawing of brick.

This SDS was prepared with information believed accurate at the time of preparation and was prepared and provided in good faith. However, General Shale Brick, Inc. assumes no responsibility as to the accuracy or suitability of such information and no warranty expressed or implied is made.